



- NOTES**
1. THE CIRCULAR GREASE TRAP SHALL BE INSTALLED AT THE PLACE WHERE IT IS NOT SUBJECTED TO VEHICULAR LOAD.
 2. INFLOW TO THE GREASE TRAP SHALL NOT INCLUDE RAIN WATER.
 3. THE OWNER/DEVELOPER SHOULD MAINTAIN THE GREASE TRAP REGULARLY TO ENSURE THAT DISCHARGE TO THE SEWER SHALL CONTAIN NO MORE THAN 50mg/l OF GREASE OR OIL.
 4. OIL, GREASE, SLUDGE ETC. COLLECTED IN THE GREASE TRAP SHALL BE REMOVED AND DISPOSED OF ONLY BY LICENSED WASTE COLLECTOR.
 5. SOLID WASTE TRAPPED BY SCREEN & STRAINER SHALL BE REMOVED FREQUENTLY AND DISPOSED OF PROPERLY.

DETAILS OF PRECAST COVER SLAB WITH LIFTING RING
SCALE 1:10

ALL DIMENSIONS ARE IN mm.

ISSUED : DEC 2021	SCALES 1 : 15 UNLESS OTHERWISE STATED
LAST REVIEWED : NOV 2021	

STANDARD GREASE TRAP
(CAPACITY EQUIVALENT TO NS 2 OF BS EN 1825)

OPUB SINGAPORE'S NATIONAL WATER AGENCY
WATER RECLAMATION (NETWORK) DEPARTMENT
DRG. NO. PUB/WRN/STD/0418

[ORIGINAL BORDER SIZE 810mm x 565mm]